ECOMAT PLUS



ECOMAT PLUS

Economical semi-automatic Ecomat wrapping machines are reliable, safe and easy to use.



Efficiency

- Motorized Power Pre Stretch System (260 %)
- Stepless film-tension control
- All types of power pre-stretch films can be used (i.e. Mima Films UP, BH)
- Minimum consumption of film per pallet
- · Optimisation of cost per pallet

Safety

- Film carriage inside the tower
- Safe, fast and ergonomic film loading
- · Control for door opening
- Emergency stop



Simplicity

- Fast and simple installation
- Safe transportation (machine packed in a wooden crate)
- Easy maintenance
- Height sensoring by photocell (wrapping of black goods also possible)
- Easy film feeding the film is just placed in the middle of the carriage and threaded through the threading slot



Easy to use

- Adjustable number of top and bottom wraps
- Adjustable carriage and turntable speed
- Support layer function
- Soft START/STOP
- Indexed stop
- 15 easily adjustable memorizable programs
- Adjustable "over the pallet" wrapping



Options

- Access ramp
- Pit foundation template
- Load stabilizer
- Turntable diameter 2 m

Technical data

Capacity

Power supply Turntable speed **Turntable height** Film carriage Machine dimensions:

Turntable Ø: Space required:

Machine weight: Wrapping height: Max. pallet weight:

Pallet dimensions:

15 - 25 pallets/h

(depending on pallet dimensions)

220-240V/50Hz

2-12 rpm 80 mm

variable climbing speed

2575 x 1650 mm

1650 mm

4.3 m² (height 2900 mm)

approx. 430 kg 2400 mm

2000 kg

L =1200 mm, W=1200 mm, H=2400 mm

