





IS DURABLE AND EASY TO USE

Rolle 9 is the best choice for a wrapping machine, especially when the ease of use and durability are important.

Quick and easy to use

- Simply select light or strong wrapping and then press the start button.
 - If necessary, the wrapping can be paused using the pause function. This is useful for loading products or fitting a top sheet.
 - A photocell automatically recognizes the height of the pallet.
 - The film roll is easy to change.

Pre-stretching of the wrapping film brings significant savings

Efficient motorized Power Pre Stretch system.

Fixed pre stretch level, up to 300 %.

- Consistency of film consumption.
- Consistency of packaging quality.

The tension of the wrapping film is easy to adjust

- Suitable tension for each product.
 - The tension of wrapping film may be easily adjusted to suit the wrapping required by the product and the desired stability during transport.
 - The film can be fed manually with the help of a button in order to attach the film to the product pallet.

Turntable

- The rotation of the table is controlled with a frequency converter, which reduces mechanical stress and maintenance.
 - The stepless adjustment of the rotation speed and the soft start enable the wrapping of even unstable product pallets.
 - The turn table always stops in the same location that enables the use of a ramp, which is available as an option.
 - Available also as an FS version, enabling the use of pallet jacks.

Technical specifications

Power supply 220–240 V / 50 Hz
Machine dimensions 2575 x 1650 mm

Max height 3000 mm

Turntable Ø 1650 mm

Turntable height 80 mm

Weight 390 kg

Rotation speed 1–11 rpm

Max pallet load dim. 1200 x 1000 mm

Wrapping height 500–2600 mm

Max. pallet load weight 1200 kg

Film reel Ø <260 mm

The compact Rolle 9 is easy to transport and install.



Machines & Service

SIGNODE INDUSTRIAL GROUP